

Ships  
with Print  
Software



## Epson SureColor S60660L

- Produce durable outdoor signs and banners, front and back-lit displays, wall and floor decals, vehicle wraps and POS, with superior image quality... quickly and efficiently
- Ultra low running cost with reduced power consumption, ink consumption, and ink cost
- Compatible with coated and uncoated paper, vinyl, canvas, film, mesh, and synthetic stocks
- Superior image quality with outstanding resolution, gamut, and gloss levels
- Proven production platform with exceptional reliability, colour accuracy, and print linearity
- Supports same day and/or overnight job turnaround
- Efficient roll-to-roll production with a bulk ink CISS, integrated dryer, and ATU
- Easy to install and can be run from a standard amperage 240V power supply
- Low maintenance with self cleaning printhead and air filtration system
- Ships complete with easy to use Epson Edge Print software
- Comprehensive warranty (includes print heads) with service cover extendable up to 5 YEARS

# Epson SureColor SC-S80660L

## Product Specifications

PRINT SYSTEM	
Print Engine	Self-cleaning DUAL PrecisionCore™ TFP with Variable Sized Dot Technology (VSDT) and integrated head guard, Epson Precision Dot Technology, PANTONE™ certified <sup>2</sup>
Media Handling	Downloadable print profiles, auto skew correction, Advanced Auto Tension Control (Ad-ATC), integrated Auto Take Up (ATU), and Blower Dryer
Print Quality	1440 x 1440 dpi Max Res, 4.2 pl min drop size
INK SYSTEM	
Type	Epson UltraChrome® GS3 Eco-Solvent
Colour Set	C, M, Y, K, Lc, Lm, Lk, Or, Rd + (opt.) white or metal (user configurable and adjustable)
Loading	9/10 x 1.5 L Continuous Ink Supply System (CISS)
PRINT SPEEDS <sup>2</sup>	
Billboard (Quality 9c)	52.3 m <sup>2</sup> /h
Banner (9c)	31.6 m <sup>2</sup> /h
Vinyl, Canvas and Paper (9c)	13.2 m <sup>2</sup> /h
Film Colour + White	3.5 m <sup>2</sup> /h
MEDIA SUPPORT	
Sizing	300-1626 mm (64") wide, 1 mm max thickness
Input	Single roll, 45 kg max weight, 250 mm max diameter
Output	Sheet (manual cut) or roll (200 mm max diameter)
Drying	Individually adjustable input, platen & output heaters
MANAGEMENT	
Features	See-through platen cover with LED lighting, 2.7" colour LCD control panel, remote e-mail status and error reporting. Ships with Epson Edge Print, Epson Edge Dashboard and Epson Accounting software.

INTEGRATION	
Space Requirements	3.6 x 2.7 x 1.7 m (WxDxH)
Operational Temp	15 to 35°C (20 to 32°C recommended)
Operational Humidity	20 to 80% (40 to 60% recommended)
Power Requirement	3 x 240V, 50/60 Hz, 5 A
Power Consumption	685 W Operating/ 25 W Sleep
Operational Noise	60.5 dB
Connectivity	USB2.0, 100BASE-TX/1000BASE-T
OPTIONS	
1YWSCS80660L	1 Yr CoverPlus On-site Service Extension
2YWSCS80660L	2 Yr CoverPlus On-site Service Extension
CONSUMABLES	
C13T724100	Cleaning kit
C13S210093	User maintenance parts kit
C13T699300	Ink cleaner
C13T45M192~992	1.5 L colour ink bags
C13T45MA92	1.5 L white ink bag
C13T45MB92	500 ml metal ink bag
C13T833092	700 ml cleaning fluid bag
C13S210071	Replacement 4 L Waste Ink Tank
CONFIGURATION OPTIONS	
SCS80660L1YR	Printer with 1 Yr On-site Warranty
SCS80660L3YR	Printer with 1 Yr Wty and 2 Yr On-site CoverPlus
SCS80660L5YR	Printer with 1 Yr Wty and 2 x 2 Yr On-site CoverPlus

<sup>1</sup> Certified 98.2% PANTONE® on ILFORD Nano Solvent Premium Photo Paper Gloss at 1440 x 1440 dpi 36 pass and 96.5% on Avery MP11105 at 1440 x 1440 dpi 36 pass. Results achieved using different print modes and different media types may vary.


<sup>2</sup> Figures are maximum engine speeds only. They do not include provisions for image processing, transfer, drying or post production. Nominated speeds may not be suitable for all media types and/or applications. Alternate print modes may be employed by RIP s/w for different results.



15 L CISS and 4 L waste system combine with a high capacity roll feed, a high precision ATU, and Blower Dryer for efficient roll to roll production.



Advanced tracking and tension control enables output with outstanding linearity and parallelism to suit the most demanding applications including tiling.



The auto head cleaning and filtration systems work with the head guard to ensure superior reliability with low maintenance and reduced cost.

## Better Products for a Better Future

Epson, SureColor, UltraChrome, PrecisionCore are registered trademarks of Seiko Epson Corporation. PANTONE® is the property of Pantone LLC. All other names and logos herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. Specifications are subject to change without notice; customers should review material posted on the web sites listed below for the latest information.

February 2020



The printer can be managed through the control panel or via Epson Edge Dashboard complete with downloadable print and media profiles, remote e-mail status and error notifications. Epson Edge Print software is powerful yet simple to use with advanced on-screen visualisation.



## FUJIFILM

For more information or detailed product specification, please call or visit us at

**FUJIFILM Business Innovation Australia Pty Ltd**

8 Khartoum Road MACQUARIE PARK NSW 2113 Australia | Tel. +61 2 9856 5000 | [fujifilm.com/fbau](http://fujifilm.com/fbau)

FUJIFILM and FUJIFILM logo are registered trademarks or trademarks of FUJIFILM Corporation. V1.0 April 2021