



- CERTIFIED
OPTICAL BONDING
- 11**
android
- ANDROID SAFE MODE**
- HYBRID SOLUTION**
- EMBEDDED BLUE LIGHT FILTER**
- ANTIMICROBIAL GLASS**
- FREE TOOLS & APPS**

Q⁺ SERIES

- 65"
- 75"
- 86"

ALL-IN-ONE SOLUTION FOR COLLABORATION
 Designed for corporate workspace, Newline Q⁺ Series brings you immersive and effective meetings. With a camera, 8-microphone array and speakers, all integrated into an interactive display, experience meetings and interact without limitations.

- 
 Broad Compatibility
- 
 Secure User Profiles
- 
 SDM-S Ready
- 
 Wi-Fi 6
- 
 High Quality Sound
incl. Subwoofer
- 
 Powered USB Type-C

Q⁺ SERIES SPECIFICATION

Product Information	Model Name	TT-6522Q	TT-7522Q	TT-8622Q
Display Specifications	Active Screen Size	65"	75"	86"
	Display Technology	LED		
	Resolution	3840 × 2160 (4K)		
	Display Area	1428 × 804 mm	1650 × 928 mm	1895 × 1066 mm
	Display Ratio	16:9		
	Display Color Depth	1.07 Billion		
	Brightness	400 cd/m ²		
	Contrast Ratio (Dynamic)	5000:1		
	Response Time	Typ. 8ms, Max. 10ms		
	Viewing Angle	178°		
	Display Life Time (MTBF)	≥ 50,000 hours		
Power	Working Voltage	AC 100 - 240V Max 5.7A	AC 100 - 240 V Max 6.5A	AC 100 - 240V Max 6.7A
	Max Power Consumption	≤ 570W	≤ 650W	≤ 670W
	Eco Power Consumption	< 150W	< 240W	< 270W
	Standby Power Consumption	< 0.5W	< 0.5W	< 0.5W
Transportation/ Storage	Storage Temperature / Humidity	-20° - 60° / 0% - 90% RH (Non-Condensing)		
	Working Temperature / Humidity	0° - 40° / 20% - 80% RH (Non-Condensing)		
	Mounting (Optional)	Wall-Mounted / Mobile Stand		
	Outline Dimensions	1513 × 926 × 116 mm	1735 × 1050 × 116 mm	1981 × 1190 × 116 mm
	Packing Dimensions	1640 × 1036 × 207 mm	1859 × 1160 × 227 mm	2119 × 1290 × 250 mm
	Net Weight	39 kg	50 kg	65 kg
	Gross Weight	49 kg	64 kg	82.5 kg

Touch	Touch Sensor	IR	Embedded Operating System	Chipset	Amlogic 311D2
	Touch Surface Technology	Anti-Glare + Anti-Fingerprint + Antimicrobial Tempered Glass		RAM	8GB
	Transparency	88% ± 3		ROM	64GB
	Surface Hardness (Mohs)	3H		External Memory	64GB (SD Card)
	Touch Points	20 Points		OS Version	Android 11
	Touch Screen Writing Tools	Passive Pen / Fingers		Multimedia File Formats Support	Image: JPEG, BMP, PNG Video: MPEG1, MPEG2, MPEG4, SorensonH.263, H.264, HEVC/H.265, MVC, AVS, AVS+, WMV3, VCL, Motion JPEG, VP8, VP9, RV30/RV40 Audio: MPEG1/2, @LAYER1/@LAYER2/@LAYER3, EAC3, ACC-LC, HEAAC, VORBIS, LPCM, IMA-ADPCM, MS-ADPCM, G711 A/MU-LAW, LBR(COOK), FLAC
Connectivity	USB Data Ports	1 × USB Type-C (PD 100W) 1 × USB 3.0 Type-C (No PD) 4 × USB Type-B (Touch) 3 × USB 3.0 Type-A 1 × USB 3.0 Type-A to Android	Speaker	Position	Bottom Front
	Digital Audio-Video Inputs	3 × HDMI In 2.0 1 × DisplayPort 1.2 1 × Microphone In		Rated Impedance	6Ω
	Digital Audio-Video Outputs	1 × HDMI Out 2.0 1 × Audio Line Out 1 × S/PDIF		Frequency Response	250Hz - 20KHz when SPL is -10dB
	Integrated PC Slot	1 × OPS-PC Slot 1 × SDM-S Slot		Output S.P.L.	80 ± 3dB
	Control Input	1 × RS-232	Max Power Output	20W × 2	
	Network	1 × In & 1 × Out RJ-45 Connector	Woofers	Position	Back Center
	Proximity Sensor	2		Rated Impedance	4Ω
	Wi-Fi Module Slot	1		Frequency Response	20Hz - 20KHz when SPL is -10dB
	Camera Module			Output S.P.L.	77 ± 2dB
				Max Power Output	15W × 1
			Camera Resolution	4K@30Hz / UHD	
			Field of View	120° FOV Lenses	
Microphone			Resolution	8m	
			Camera Tile Range	15°	
			Position	Upper Front	
			Quantity	8-Mic Array	
			Pickup Distance	8M	

FUJIFILM | newline

20E Pasir Panjang Road , #08-21, Mapletree Business City, Singapore 117439
fujifilm.com/fbglobal